


HAND BEVELER Model **HB-15B** *Chamfering up to 15C*



- Ideal for chamfering before welding
- Use easy-to-replace cutting blades
- Each cutting blade has four working edges for good economy
- Finish a surface so fine that post-sanding is unnecessary
- Column R-section can be chamfered with optional attachment
- No damage of workpieces is expected as heat-hardening or oxidization will seldom happen

Specifications

Model	HB-15B	
Power Source (Single phase)	115 V AC, 50/60 Hz	230 V AC, 50/60 Hz
Rated Power Consumption	W 910	910
Rated Current	A 10.5	4
No-load Speed	min ⁻¹ (rpm) 3,340	2,750
Chamfering Capacity	0C - 15C	
Chamfer Angle	15° - 45°	
Mass (Weight)	kg 14	

Standard accessories

- Hex. Socket Screw Key 4,5,6 mm : each 1 pc.
- Spanner 24 × 27 : 1 pc.
- Hook spanner 25 - 28 : 1 pc.
- 3 mm T Wrench Key : 1 pc.
- TA9A093 Cutting Blade 12.7 sq. 1 set (12 pcs./ set)

Optional accessories

- TA9A728 Pipe Plate Ass'y for 5" to 32" (125 mm to 800 mm)

Chamfer angle and width

Chamfer Angle α	HB-15B Mild Steel(mm)		Chamfer X Y	Straight
	X	Y		
45°	15	15		
30°	9	15.5		
15°	4	15.4		

Handy Electric Chamfering Tool

MINI BEVELER Model **MB-03A**

Double insulation



Compact and light for speed chamfering

- An outer R-part attachment allows chamfering of outer diameters with a radius greater than 170 mm.
- An optional inner head ass'y allows chamfering a pipe of inner diameter larger than 100 mm (50R).

Specifications

Model	MB-03A	
Power Supply (Single phase)	230 V or 115 V AC, 50/60 Hz	
Rated Power Consumption	W 430	
Rated Current	A 2 / 4.5	
Chamfering Capacity	0C - 3C	
Chamfering Radius Capacity	2R, 3R	
Chamfer Angle	45°	
Rated Revolutions	min ⁻¹ (rpm) 7,100	
Mass (Weight)	kg 2.5	

Standard accessories

- 3 & 4 mm Hex. Socket Screw Key : each 1 pc.
- Spanner T-9F : 1 pc.

Optional accessories

- TA9A386 Cutting Blade 9.525, 10 pcs./set
- TA9A592 Cutting Blade 9.525 2R, 10 pcs./set
- TA9A638 Cutting Blade 9.525 3R, 10 pcs./set
- TA9A594 Inner Head Ass'y

Chamfer angle, width and radius

Chamfer Angle α	MB-03A Mild Steel(mm)		Chamfer X Y	Straight	
	X	Y			
45°	3	3			
		Radius			Round
Model	MB-03A				
Material	Mild Steel				
Radius(mm)	2, 3				